

**SRK-ZSH-WF SINGLE-SPLIT WALL MOUNTED TYPE**

**3 YEARS**  
**Warranty**



**SRK20,25,35,50ZSH-WF**




**BUILT IN WIRELESS LAN**




**Wireless remote control**



**Made in Thailand**



**SRC20,25,35ZSH-W**



**SRC50ZSH-W**

**FUNCTIONS**

**ENERGY SAVING**



**AIR FLOW**



**CLEAN OPERATION & FILTER**



**COMFORT & CONVENIENCE**



**OTHERS**




**SPECIFICATIONS**

		3/4 HP		1 HP		1.5 HP		2 HP	
		SRK20ZSH-WF		SRK25ZSH-WF		SRK35ZSH-WF		SRK50ZSH-WF	
		SRC20ZSH-W		SRC25ZSH-W		SRC35ZSH-W		SRC50ZSH-W	
Power source		1 Phase, 220 - 240V, 50Hz							
Nominal cooling capacity (Min-Max)	kW	2.0 (0.9 - 2.9)	2.5 (0.9 - 3.1)	3.5 (0.9 - 4.0)	5.0 (1.3 - 5.5)				
Nominal heating capacity (Min-Max)	kW	2.7 (0.9 - 4.3)	3.2 (0.9 - 4.5)	4.0 (0.9 - 5.0)	5.8 (1.3 - 6.6)				
Power consumption	Cooling/Heating	kW	0.44 / 0.59	0.62 / 0.74	0.89 / 0.94	1.35 / 1.56			
EER/COP	Cooling/Heating		4.55 / 4.58	4.03 / 4.32	3.93 / 4.26	3.70 / 3.72			
Max. running current		A	9	9	9	14.5			
Sound power level	Indoor	Cooling/Heating	48 / 50	50 / 53	54 / 56	59 / 60			
	Outdoor	Cooling/Heating	56 / 56	56 / 58	61 / 61	61 / 63			
Sound pressure level	Indoor	Cooling (Hi/Me/Lo/Ulo)	34 / 25 / 22 / 19	36 / 28 / 23 / 19	40 / 30 / 26 / 19	46 / 36 / 29 / 22			
		Heating (Hi/Me/Lo/Ulo)	36 / 29 / 23 / 19	39 / 30 / 24 / 19	41 / 36 / 25 / 19	46 / 37 / 31 / 24			
	Outdoor	Cooling/Heating	45 / 45	46 / 46	50 / 48	51 / 52			
		Air flow	Indoor	Cooling (Hi/Me/Lo/Ulo)	9.3 / 7.0 / 5.9 / 5.0	9.9 / 8.0 / 5.9 / 5.0	11.3 / 8.7 / 7.0 / 5.0	12.1 / 9.9 / 7.4 / 5.9	
Exterior dimensions	Indoor / Outdoor	Height x Width x Depth	mm	290 x 870 x 230					
				540 x 780(+62) x 290				595 x 780(+62) x 290	
Net weight	Indoor / Outdoor	kg	9.5 / 31.0		9.5 / 34.5		10.0 / 36.0		
Refrigerant	Type/GWP		R32 / 675						
	Charge	kg/TCO <sub>2</sub> Eq	0.62 / 0.419		0.78 / 0.527		1.05 / 0.709		
Refrigerant piping size	Liquid/Gas	ø mm	6.35(1/4") / 9.52(3/8")				6.35(1/4") / 12.7(1/2")		
Refrigerant line (one way) length [chargeless length]		m	Max.20 [15]				Max.25 [15]		
Vertical height differences	Outdoor is higher/lower	m	Max.10 / Max.10				Max.15 / Max.15		
Outdoor operating temperature range	Cooling	°CDB	-15 to 46						
	Heating		-15 to 24						
Clean filter			Allergen Clear Filter x1, Photocatalytic Washable Deodorising Filter x1						

\* The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

\* Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

\* The above specifications are subject to change without prior notice.



**Wo Kee Hong Limited**

Hong Kong Office

+ 852 2514 4700

Unit 3302, 33/F, Cable TV Tower,  
9 Hoi Shing Road, Tsuen Wan, N.T., H.K.

wokeehong-mhi.com.hk

Macau Office

+ 853 2876 8155

Rua de S. Domingos No. 16F-16L, Centro  
Comercial, Hin Lei 5 Audar 63 Room, Macau

info@wokeehong.com.hk



Website



Warranty  
Registration